



G-TURBO 90S/2

(2 Color Pad Printer)




PLC control touch screen panel



2 independent pad cylinders




Platform in / out movement & pad clean underneath design for max. product size



Stable granite stone machine structure



2 color pneumatic shuttle



Maximum space for product/image with advantage of auto pad clean function

FEATURES

- 2 color automatic pad printer
- 2 color pneumatic shuttle attachment
- Granite stone machine structure for performance & stability as well as protect our environment
- Wide machine stand
- Two independent pad cylinders
- Platform in/out movement
- Pneumatic power machine operation
- Use sealed TCIC / Green cup set up
- Able to use laser engraved Green plate, thin steel plate and polymer plate
- Dead-on printing plate registration for quick job change
- PLC control touch screen panel
- Automatic pad clean with programmable cleaning cycle
- Pad stroke & speed adjustment
- Special functions: double ink / print cycles, dwell and delay before print
- Digital pad stroke (DPS) for variable printing depth
- Hardened ground steel shaft with impregnated bushing ensure friction-free movement
- High speed and smooth machine operations

SPECIFICATIONS

Ink cup size :	Ø60, 70 & 90 mm x 2
Printing plate size :	100 x 250 mm x 2
Max. speed : (dry cycle) *	900 / hr.
Pad compression :	753N x 2
Pad cylinder :	Ø40 x 125 mm x 2
Pad carriage stroke (in/out) :	180 mm
Power :	110/220V
Air consumption :	160 litre/min. (approx.)
Accuracy +/- :	0.05 mm
Size : (L x W x H)	830 x 760 x 1,480 mm
Weight :	270 kg (approx.)

* Please note that actual output may be affected by print requirement, ink drying condition, load/unload arrangement, pad stroke speed, pad hardness, production setup, product quality and production control.

KENT

www.kentpp.com

122M-1111

